





Sportelli • Hatch-doors

SPORTELLI PER BANCHI A BASSA TEMPERATURA (-16/-18°C) CON **CAVO TERMICO RISCALDANTE 220 VOLT**
 HATCH-DOORS FOR LOW TEMPERATURE COUNTERS (-16/-18°C) WITH **220 VOLT HEATING RESISTOR**



Dettaglio passaggio cavo termico nel retro cornice
 Detail of the passage of the heat cable in the back of the framework



Articolo • Item	W watt	A mm	B mm	C mm	S mm	S1 mm	G mm	G1 mm	L* mm	H* mm
8SS30/BT	23	471	334	17	50	6	268	405	442	305
8SS40/BT	28	471	443	17	50	6	367	405	442	404
8SS44/BT	28	471	471	17	50	6	405	405	442	442
8SS50/BT	29	471	531	17	50	6	465	405	442	502
8SS60/BT	33	471	631	17	50	6	565	405	442	602
8SS70/BT	36	471	731	17	50	6	665	405	442	702

sportelli orizzontali • horizontal doors

8SS50/HORIZ/BT	29	531	471	17	50	6	405	465	502	442
8SS60/HORIZ/BT	33	631	471	17	50	6	405	565	602	442

Dimensioni: vedi legenda a pag. 25
 Sizes: see please the legend at page 25

* tolleranza • tolerance -0 / +1 mm



SX Cerniera sinistra / Left hinge
DX Cerniera destra / Right hinge

Specificare in fase d'ordine la posizione delle cerniere (destra o sinistra)
 Please specify the hinge position (left-hand or right-hand side) at purchase order